

Docket No.: 4590-397

RECEIVED  
CENTRAL FAX CENTERPATENT

JUN 14 2007

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended): An electronic component mounted in an individual package and intended to be connected to other components of an electronic system, said electronic component comprising:

one or more integrated circuit chips working around a main millimetric frequency  $F$  greater than 45 GHz, wherein said package has at least two ports for communicating electrical signals between the interior and the exterior of said package, the first port being a port with transition by contactless electromagnetic coupling for the transmission of signals at the main working frequency greater than 45 GHz, and the second port being a port with microstrip or coaxial type transition for the transmission of a ~~working~~ main frequency  $F/N$  that is a subharmonic of the main frequency  $F$  where  $N$  is  $\geq 2$ .

2. (Currently Amended): The component as claimed in claim 1, wherein the package is provided with a conductive cover positioned at a distance from the first port such that said conductive cover sets up, above this port, an electromagnetic short circuit at the main ~~working~~ frequency, thus forming a wave reflector facilitating the transmission of ~~this~~ said main frequency through the first port.

3. (Currently Amended): The component as claimed in claim 2, wherein the conductive cover is at a height above the port equal to a quarter of the wavelength, or an odd multiple of the quarter of the wavelength of the ~~working~~ main frequency.

4. (Currently Amended): The component as claimed in claim 1, wherein one of the chips included in said package comprises means ~~ef~~ for multiplying frequency ~~in~~ by a ratio  $N$  to change from the subharmonic frequency to the main ~~working~~ frequency.

Docket No.: 4590-397

PATENT

5. (Currently Amended): The component as claimed in claim 1, comprising a ceramic substrate, a first metallized side of which is etched to form a microstrip line having a free end and another side of ~~which~~ the ceramic substrate is also metallized to form a ground plane, the ground plane being interrupted facing the free end, to provide the contactless electromagnetic coupling between the interior and the exterior of the package via the microstrip free end.

6. (Currently Amended): The component as claimed in claim 5, wherein a conductive cover is at a height above the free end of the microstrip line equal to a quarter of the wavelength, or an odd multiple of a quarter of the wavelength of the ~~working~~ main frequency.

7. (Previously Presented): The component as claimed in claim 5, comprising a metallic base open facing the microstrip free end.

8. (Currently Amended): The component as claimed in claim 1, comprising one or more MMIC chips fixed on a base, one of the chips including a microstrip line, ~~of which~~ having one free end which is used as a the contactless electromagnetic transition, said one chip extending over an opening in the base so that the free end of the line is located in line with the opening, in order to form a the contactless electromagnetic transition through ~~this~~ the opening.

9. (Currently Amended): The component as claimed in claim 2, wherein one of the chips included in said package comprises means ~~of~~ for multiplying frequency ~~in~~ by a ratio N to change from the subharmonic frequency to the main ~~working~~ frequency.

10. (Currently Amended): The component as claimed in claim 3, wherein one of the chips included in said package comprises means ~~of~~ for multiplying frequency ~~in~~ by a ratio N to change from the subharmonic frequency to the main ~~working~~ frequency.

11. (Previously Presented): The component as claimed in claim 2, comprising a ceramic substrate, a first metallized side of which is etched to form a microstrip line having a free end and another side of which is also metallized to form a ground plane, the ground plane being interrupted facing the free end, to provide contactless electromagnetic coupling between the

Docket No.: 4590-397

PATENT

interior and the exterior of the package via the microstrip free end.

12. (Previously Presented): The component as claimed in claim 3, comprising a ceramic substrate, a first metallized side of which is etched to form a microstrip line having a free end and another side of which is also metallized to form a ground plane, the ground plane being interrupted facing the free end, to provide contactless electromagnetic coupling between the interior and the exterior of the package via the microstrip free end.

13. (Previously Presented): The component as claimed in claim 4, comprising a ceramic substrate, a first metallized side of which is etched to form a microstrip line having a free end and another side of which is also metallized to form a ground plane, the ground plane being interrupted facing the free end, to provide contactless electromagnetic coupling between the interior and the exterior of the package via the microstrip free end.

14. (Previously Presented): The component as claimed in claim 6, including a metallic base open facing the microstrip free end.

15. (Currently Amended): The component as claimed in claim 2, including one or more MMIC chips fixed on a base, one of the chips including a microstrip line, ~~of which~~ having one free end which is used as a the contactless electromagnetic transition, said one chip extending over an opening in the base so that the free end of the line is located in line with the opening, in order to form a the contactless electromagnetic transition through ~~this~~ the opening.

16. (Currently Amended): The component as claimed in claim 3, including one or more MMIC chips fixed on a base, said one of the chips including a microstrip line, ~~of which~~ having one free end is which used as a the contactless electromagnetic transition, ~~this~~ said one chip extending over an opening in the base so that the free end of the line is located in line with the opening, in order to form a contactless electromagnetic transition through ~~this~~ the opening.

Docket No.: 4590-397

PATENT

17. (Currently Amended): The component as claimed in claim 4, including one or more MMIC chips fixed on a base, said one of the chips including a microstrip line, ~~of which~~ having one free end which is used as a the contactless electromagnetic transition, ~~this~~ said one chip extending over an opening in the base so that the free end of the line is located in line with the opening, in order to form a the contactless electromagnetic transition through ~~this~~ the opening.